

SIGRAFLEX® HOCHDRUCK FLAT GASKET WITH INNER AND OUTER EYELET

3885FD30

Base material is SIGRAFLEX® Hochdruck. Additionally the gasket also has inner and outer eyelet. This gasket type has been especially designed for tongue and groove flanges.



Operational Data

Temperature	450 °C
Temperature [min]	-269 °C
Temperature [max]	550 °C
Pressure [max]	250 bar

Dichtungskennwerte ASME

m	2
Y [PSI]	7300

Approvals and Test Reports

TA Luft 2002 [VDI 24A0/2200]

Fire Safe Test

VdTÜV Merkblatt Dichtung 100

BAM oxygen

BAM oxygen [liquid]

Gas [DIN 3535-6]

EG 1935/2004

Flanschformen

Nut and spring [form TG]

Preliminary jump [form SR]

Apparatus

Bridges

This datasheet on the internet: <https://idt-gaskets.com/products/gaskets/61f7e49969a322f5c>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scope. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT

Essen: +49 [2 01] 8 55 11-0 · Annaberg-Buchholz: +49 [37 33] 5 05-0 · München: +49 [89] 99 18 83-0
Further sealing systems and technical information can be found [idt-gaskets.com](https://www.idt-gaskets.com)

Last Changed 2023-02-03