

UNISEAL® 3400 FLAT GASKET

3400FD01

This fibre seal is made from aramid fibres and inorganic fillers in a high-strength connection via chemical elastomers.



Operational Data

Temperature [min]	-50 °C
Temperature [max]	200 °C
Pressure [max]	100 bar

Dichtungskennwerte EN 13555

Dichtungskennwerte 2 mm [Amtec]

https://idt-gaskets.com/download/dichtungskennwerte/0000_292

Dichtungskennwerte DIN 2505 V

$K_0 \times K_d$ [N/mm]	$29 \times b_d$
k_1 [mm]	$2 \times b_d$

Dichtungskennwerte ASME

m	3
Y [PSI]	4300

Approvals and Test Reports

TA Luft 2002 [VDI 24A0/2200]

DIN EN13555 [TA Luft 2021]

Fire Safe Test

Leaflet

Gas [DIN 3535-6]

Gas [DIN 30653 (ehemals VP401; HTB)]

WRAS

Food [FDA]

This datasheet on the internet: <https://idt-gaskets.com/products/gaskets/61f7e4a8b3c66bcf4>

General information: All information given in this Technical Information sheet represents our current level of knowledge and serves as information on our products and their respective scope. It is not meant to ensure any particular properties of any product or the suitability of any product for any specific application, neither does it create any liability on our part. © Copyright by IDT

Essen: +49 [2 01] 8 55 11-0 · Annaberg-Buchholz: +49 [37 33] 5 05-0 · München: +49 [89] 99 18 83-0
Further sealing systems and technical information can be found [idt-gaskets.com](https://www.idt-gaskets.com)

Last Changed 2023-02-03